

# ENVIRONMENTAL SAFETY & COMPLIANCE

Our product ensures safety and environmental responsibility through the following features:

- **Heavy Metal-Free:** No detectable levels of harmful heavy metals (lead, cadmium, mercury, hexavalent chromium).
- **Formaldehyde-Free:** Does not release formaldehyde (HCHO), preventing sick building syndrome.
- **Low VOC Emissions:** Minimal volatile organic compounds (TVOC, toluene), reducing odor and ozone generation.
- **Safety Standards:** Complies with KC mark standards for wallpaper and paperboard.
- **Children's Safety:** Meets safety requirements for hazardous chemicals in children's products.
- **Antibacterial and Antifungal:** Offers excellent antibacterial and antifungal properties, maintaining a comfortable environment.





Heavy Metals [Pb, Cd, Hg, CrVI]		Formaldehyde [HCHO][HCHO]		Phthalates	
<b>standard</b> [Pb] 5mg/kg [Cd] 0.5mg/kg [Hg] 2mg/kg [CrVI] 1mg/kg	<b>Not detected</b>	<b>standard</b> 0.12mg/m <sup>3</sup> h	<b>Not detected</b>	<b>standard</b> [DEHP] 0.1% or less [DBP] 0.1% or less [BBP] 0.1% or less	<b>Not detected</b>

## Safety and Compliance for Children's Products

Our product adheres to the following safety standards:

- **Common Safety Standards:** Meets all relevant safety standards for children's products.
- **Hazardous Chemicals Elution:** Complies with stringent elution standards for hazardous chemicals, ensuring minimal risk to children's health and safety.

Common safety standards for children's products		Elution standards for hazardous chemicals	
<b>standard</b> [ Sb ] 60mg/kg [ As ] 25mg/kg [ Ba ] 1000ng/kg [ Cd ] 75mg/kg	<b>satisfy</b>	<b>standard</b> [ Cr ] 60mg/kg [ Pb ] 90mg/kg [ Hg ] 60mg/kg [ Se ] 500 mg/kg	<b>satisfy</b>

### Flame retardant performance

[Fire Industry Technology Institute Certification]







Carbonization length | Carbonization area | Afterflame time | Afterflame time | Smoke density

below	below	below	below	below
20cm	30cm <sup>2</sup>	3 seconds	5 seconds	200 Ds

 Flame retardant certification

소방산업기술원

### Staining resistance

					
soy sauce	Cola	10% hydrochloride	coffee	5% ethanol	vinegar

No change

# BODAQ INTERIOR FILM: AN ECO-FRIENDLY FINISHING SOLUTION

## SAFE SOLUTION



NO HEAVY METALS



NO FORMALDEHYDE



NO VOC



CLASS I OR A  
FIRE- & SMOKE-RATING

## HEALTHY SOLUTION



ATOPY SAFE FOR BABIES



ANTIFUNGUL



ANTIBACTERIAL



NON-TOXIC

## ENVIRONMENTAL SOLUTION



ECO-FRIENDLY CERTIFICATION



LESS CO2 EMISSIONS



LESS WASTE



HEALTHY BUILDING MATERIAL CERTIFICATION



KOREA ECO-LABEL



ECO-HOUSING LABEL

